

# 産業用サーバ用シャーシ タワー型



高さ(1U = 1.75")		Tower		
モデル名		<a href="#">HPC-2040</a>	<a href="#">HPC-5000</a>	<a href="#">HPC-7000</a>
ボード対応フォームファクタ		Mini iTX	Micro ATX	Micro ATX, ATX, EATX
総スロット数 / 高さフルサイズカード対応スロット数		1/0	4/2 (11.73" Length)	7/6
ドライブベイ	Slim ODD Bay	1	1	1
	5.25" (front-accessible)	-	-	-
	3.5" (hot-swappable)	4 (3.5" / 2.5")	-	-
	3.5" (internal)	-	2 x 3.5" or 1 x 3.5" + 1 x 2.5"	3 (External)
	2.5" (hot-swappable)	-	-	-
	2.5" (internal)	1	-	-
放熱	Chassis Fan	1 (12cm / 57.2CFM)	1 (12cm / 82CFM)	2 (12cm/150CFM)
	Air Filter	-	Yes	-
前面I/O	USB 3.0	2	2	2
	USB 2.0	-	2	-
電源	Single Power Supply	250W	300W/500W	500W/1200W
	Redundant Power Supply	-	-	-
その他	LED Indicators	Power, LAN 1, LAN 2, HDD, System Information	System: Power	System: Power
	Rear Panel	One reserved DB-9 ports	Two reserved DB-9 ports	Two USB reserved ports
耐環境性	Operating Temperature	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)
	Non-Operating Temperature	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)
	Operating Humidity	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing
	Non-operating Humidity	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing
サイズ	Dimensions (W x H x D)	210 x 230 x 275 mm (8.3" x 9.1" x 10.8")	192 x 376.7 x 338.5 mm (7.56" x 14.83" x 13.33")	267.1 x 458 x 500 mm (10.52" x 18.03" x 19.69")

## 19インチラックマウント型(1~3U)



高さ(1U = 1.75")		1U	2U		3U/Tower
モデル名		<a href="#">HPC-7120S</a>	<a href="#">HPC-7242</a>	<a href="#">HPC-7282</a>	<a href="#">HPC-7320</a>
ボード対応フォームファクタ		Micro ATX, ATX	Micro ATX, ATX	Micro ATX, ATX	Micro ATX, ATX, EATX
総スロット数 / 高さフルサイズカード対応スロット数		1/0	3/3	7/0	7/6
ドライブベイ	Slim ODD Bay	-	1	1	1
	5.25" (front-accessible)	-	-	-	-
	3.5" (hot-swappable)	-	4 (3.5" / 2.5")	8	2 (3.5" / 2.5")
	3.5" (internal)	-	-	2	2
	2.5" (hot-swappable)	2 (HPC-7120S-35ZXE only)	-	Optional	-
	2.5" (internal)	2	2	-	-
放熱	Chassis Fan	3 (4 cm/23.1 CFM)	1 (8 cm/47CFM) + 2 (6 cm/28CFM)	3 (8cm / 52.6 CFM)	2 (8cm/57CFM) + 1 (6cm/27.72CFM)
	Air Filter	-	Yes	-	Yes
前面I/O	USB 3.0	2	2	-	2
	USB 2.0	-	-	2	-
電源	Single Power Supply	350W/850W	350W/500W	500W/850W	500W/850W
	Redundant Power Supply	-	550W	550W/800W	550W/800W
その他	LED Indicators	System: Power, HDD, LAN1, LAN2, System Information. HDD Tray: HDD Power and Activity LED	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED
	Rear Panel	-	Two reserved DB-9 ports	-	Two reserved DB-9 ports
耐環境性	Operating Temperature	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)
	Non-Operating Temperature	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)
	Operating Humidity	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing
	Non-operating Humidity	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing
サイズ	Dimensions (W x H x D) 438 x 43 x 381 mm (17.24" x 1.7" x 15")	426.4 x 88 x 525 mm (16.79" x 3.46" x 20.67")	437 x 88.9 x 533.4 mm (17.2" x 3.5" x 21")	426.4 x 132.2 x 480 mm (16.79" x 5.2" x 18.9")	

## 19インチラックマウント型(4U)



高さ(1U = 1.75")		4U/Tower		
モデル名		HPC-7442	HPC-7485	HPC-7484
ボード対応フォームファクタ		Micro ATX, ATX, EATX	ATX, EATX	Micro ATX, ATX, EATX
総スロット数 / 高さフルサイズカード対応スロット数		7/7	11/11	7/7
ドライブベイ	Slim ODD Bay	1	1	1
	5.25" (front-accessible)	-	-	-
	3.5" (hot-swappable)	4 can upgrade to 8 (3.5" / 2.5")	8 (3.5" / 2.5")	8 (3.5" / 2.5")
	3.5" (internal)	1	-	-
	2.5" (hot-swappable)	-	-	-
	2.5" (internal)	-	2	1
放熱	Chassis Fan	1 (12cm /114 CFM) + 1 (8cm/55 CFM)	3 (12cm /238 CFM)	2 (12cm /150.33 CFM)
	Air Filter	Yes	-	Yes
前面I/O	USB 3.0	2	2	2
	USB 2.0	-	-	-
電源	Single Power Supply	500W/700W/1200W	-	700W/1200W
	Redundant Power Supply	500W	1200W/2000W	-
その他	LED Indicators	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED	System: Power, HDD, LAN1, LAN2, temperature, fan. HDD Tray: HDD Power and Activity LED
	Rear Panel	Five DB-9 ports and one 68-pin SCSI openings	Two DB-9 ports and two PS2 and two USB	Five DB-9 ports and one 68-pin SCSI openings
耐環境性	Operating Temperature	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)	0 ~ 40 °C (32 ~ 122 °F)
	Non-Operating Temperature	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)	-40 ~ 70 °C (-40 ~ 158 °F)
	Operating Humidity	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing
	Non-operating Humidity	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing
サイズ	Dimensions (W x H x D)	426 x 177 x 600 mm (16.7" x 7.0" x 23.6")	435 x 176 x 660 mm (17.1" x 6.9" x 25.9")	426 x 177 x 630mm (16.7" x 7.0" x 24.8")